

**TASKI**

**JohnsonDiversey**  
Clean is just the beginning



# Vision Matte

## Low Gloss Floor Finish



- Versatile and easy to apply.
- Maintains your floor's natural appearance.
- Recommended by leading manufacturers of linoleum and rubber flooring.
- Slip and traffic resistant.
- Provides durable protection without glare and the traditional gloss build.
- Resistant to sanitizers and disinfectants.



# Product Information

## Properties

**TASKI Vision Matte** is a versatile, user friendly low gloss “silky” floor finish that simplifies your floor care program. It is great for use in hospitals, nursing homes and schools with synthetic gymnasium flooring where high shine products are not preferred.

## Product Data

Physical State and Appearance:	Liquid. (Emulsion).
Odor:	Mild. Ammoniacal.
Color:	Milky-white.
pH:	8.55 [Basic].
Specific Gravity:	1.02.
Boiling/Condensation Point:	>100°C (212°F).
Melting/Freezing Point:	<0°C (32°F).
Vapor Density:	>1 Air = 1.
Viscosity:	5-6 cP (Dynamic).
Solubility in water:	Complete.
Coverage:	2000-2500 sq. ft. per U.S. gallon (50-60m <sup>2</sup> per liter).
Recoat Time:	30 minutes.
Slip Resistance:	0.5 minimum (ASTM D2047).

## Ecological/Safety Information

**EYE CONTACT:** Rinse immediately with plenty of water. If irritation develops, seek medical attention.

## Machines & Tools

Traditional Mop & Bucket

## Packaging

4 / 1 Gallon (3.78 L) Containers	3045546
1 / 5 Gallon (18.9 L) ENVIROBOX™	3045538

FOR COMMERCIAL & INDUSTRIAL USE ONLY  
 © 2003 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902.  
 For further information on special applications or other JohnsonDiversey products, contact JohnsonDiversey Technical Support at 1-800-558-2332 or visit our web-site at [www.johnsondiversey.com](http://www.johnsondiversey.com).  
 Printed in the U.S.A. on recycled paper from 50% total recycled fiber containing 10% post consumer wastes.

To contact your representative call:  
 US: 800 626 5015 • Canada: 800 668 7171 • Puerto Rico: 800 959 1533

3137791 SPC469 (03/227)

## Directions for Use

- Strip floor, using a **TASKI** brand heavy duty stripper, per the instructions on the stripper label. If stripping linoleum floors, use **TASKI LINOSTRIP**.
- Apply 2-3 coats using a clean mop.
- Allow 30 minutes drying time between coats. Temperatures, humidity and ventilation may affect drying time.

## Maintenance

- Dust, mop or sweep.
- Clean the floor with mop or automatic scrubber using the recommended **TASKI** brand cleaner according to label directions.

## Recoating

- Dust, mop or sweep.
- Clean the floor with mop or automatic scrubber using the recommended **TASKI** brand cleaner according to label directions.
- Apply 1 or 2 coats using a clean mop.

## Removal

- Remove using recommended **TASKI** brand stripper according to label directions.

## For Best Results

### Follow application instructions as outlined and:

- Do not dilute.
- Do not use on surfaces colder than 10°C/50°F.
- To avoid contamination, do not return unused finish to original container.
- Floors can be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials.
- Do not use on wood.
- Use for commercial and industrial purposes.

