

BARRIER

A Water-Based Impregnator for Masonry, Concrete, Natural Stone, Grout & Tile and Unglazed Ceramic.

**Preserves Natural Appearance • Protects from Stains and Soil Penetration
Floors Breathe While Easier to Clean • Penetrates and Seals • Solvent-Free • Slip Resistant • Easy to Apply**

DESCRIPTION

BARRIER is a high performance water based penetrating sealer impregnator specially designed to protect concrete, stucco, masonry surfaces, brick, clay roofing tile, unglazed ceramic and terracotta tiles, marble, granite, slate, terrazzo, sandstone, limestone, and quarry tile against stains, dust, dirt, water, and oil. **BARRIER** will not yellow or leave a surface film.

APPLICATION

1. Remove surface dirt on the surface to be treated with **BARRIER** using standard maintenance procedures.
2. Make sure the surface is completely dry before using **BARRIER**.
3. During application, make sure temperature is above 65°F and below 85°F.
4. Apply the sealer evenly over the substrate by mopping, brushing, rolling or spraying methods.
5. Let the surface cure for about 24 hours after applying the sealer.
6. For maximum protection, a second application is recommended.

PRECAUTIONS

On fresh concrete, allow 10 days after completion of work before application. Color enhancement may occur on certain types of natural stone and slate. Always test first to ensure the effect is acceptable.

COVERAGE

On polished surfaces coverage varies from 600 to 1200 square feet per gallon. More porous substrates will reduce the coverage per quart.

Please consult Material Safety Data Sheet for information concerning handling of this product.

TYPICAL PROPERTIES

Appearance	Translucent White emulsion
Odor	Acrylic
pH of concentrate	6.2 ± 0.2
Density	1.015 ± 0.005

Centaur Floor Systems
Attn: Maintenance Supply Division
135 Chapala Street
Santa Barbara, CA 93101
1-800-536-9007
805-957-0182
www.centaurmaintenancesupplies.com